

A

MODELLO <i>Type</i>	PORTATA OTTIMALE <i>Recommended Load</i> [daN]	COSTANTE ELASTICA <i>Elastic constant</i> K [daN/mm]
MOPLA 5/AY 110	110	16,9
MOPLA 5/AY 140	140	21,5
MOPLA 5/AY 160	160	24,6
MOPLA 5/AY 180	180	27,7
MOPLA 5/AY 200	200	30,8
MOPLA 5/AY 220	220	36,2
MOPLA 5/AY 240	240	36,9
MOPLA 5/AY 260	260	40,0
MOPLA 5/AY 290	290	44,6
MOPLA 5/AY 330	330	50,8
MOPLA 5/AY 380	380	58,5
MOPLA 5/AY 420	420	64,6
MOPLA 5/AY 460	460	70,8
MOPLA 5/AY 510	510	78,5
MOPLA 5/AY 540	540	83,1
MOPLA 5/AY 560	560	86,2
MOPLA 5/AY 600	600	92,3
MOPLA 5/AY 650	650	100,0
MOPLA 5/AY 690	690	106,2
MOPLA 5/AY 750	750	115,4
MOPLA 5/AY 810	810	124,6
MOPLA 5/AY 860	860	132,3
MOPLA 5/AY 920	920	141,5
MOPLA 5/AY 970	970	149,2
MOPLA 5/AY 1020	1020	156,9
MOPLA 5/AY 1070	1070	164,6