

C	MODELLO	PORTATA OTTIMALE	COSTANTE ELASTICA
	Type	Recommended Load [daN]	Elastic constant K [daN/mm]
	MOPLA 5/CY 220	220	8,1
	MOPLA 5/CY 270	270	10,0
	MOPLA 5/CY 320	320	11,9
	MOPLA 5/CY 390	390	14,4
	MOPLA 5/CY 430	430	15,9
	MOPLA 5/CY 480	480	17,8
	MOPLA 5/CY 540	540	20,0
	MOPLA 5/CY 580	580	21,5
	MOPLA 5/CY 610	610	22,6
	MOPLA 5/CY 730	730	27,0
	MOPLA 5/CY 780	780	28,9
	MOPLA 5/CY 830	830	30,7
	MOPLA 5/CY 910	910	33,7
	MOPLA 5/CY 1090	1090	40,4
	MOPLA 5/CY 1220	1220	45,2
	MOPLA 5/CY 1320	1320	48,9
	MOPLA 5/CY 1380	1380	51,1
	MOPLA 5/CY 1470	1470	54,4
	MOPLA 5/CY 1580	1580	58,5



ΓΕΩΡΓΙΟΥ ΠΑΠΑΝΔΡΕΟΥ 21 - ΧΑΪΔΑΡΙ, Τ.Κ. 124 62

www.nuovo-acoustics.gr

210 5817364

info@nuovo-acoustics.gr